

VP-810 把手式蝶閥
Butterfly Valve (Handle type)



- Pressure rating: 2"~8" 150 PSI @73.4°F(23°C)
(Standard stem: SUS 410 + heat process.
Alternative material for stem: SUS 304/316)
- Compact and light-weight design
- Low flow loss
- The scale on top of the body can clearly indicate the opening angle.
- Ideally suited in a limited piping space
- 工作壓力 : 2"~8" 150 PSI @73.4°F(23°C)
(標準中心柱材質SUS 410 + 熱處理, 亦可選用SUS 304/316 材質)
- 蝶片開啓角度可由刻度清楚顯示, 並可由齒輪片固定
- 全面型墊片密封設計, 安全性佳

Table with 8 columns: Type, Size, Standard, Material, Seat, O-ring, Disc, End type. Rows include VP-810, VP-811, VP-813, VP-814 with various material and size specifications.

Table with 10 columns: Nom., SIZE, 40mm, 50mm, 65mm, 80mm, 100mm, 125mm, 150mm, 200mm. Rows include JIS, ANSI, DIN standards and dimensions D, D2, D3, L, H, H1, H2, W1, W2, W3.

Table with 4 columns: NO, PART NAME, MATERIAL, Q'TY. Lists 24 parts including BODY, DISC, SEAT, STEM, O-RING, INSERT NUT, HANDLE, SPRING, LOCK, and RIVET with their respective materials and quantities.

